

PVCU SOLVENT CLEANER

Page: 1

Compilation date: 25/04/2008

Revision date: 26/11/2015

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PVCU SOLVENT CLEANER

Synonyms: ZSOLVSIROBULK (17A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Industrial uses: Uses of substances as such or in preparations at industrial sites. Use

in cleaning agents. Consumer uses: Private households / general public / consumers.

plastics Industry.

1.3. Details of the supplier of the safety data sheet

Company name: Edge Building Products Ltd

Blatchford Road

Horsham
West Sussex
RH13 5QR

Tel: 01403 218877 **Fax:** 01403 212500

Email: sales@edgebp.co.uk

1.4. Emergency telephone number

Emergency tel: 01403 218877 (Office Hours Only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Asp.

Tox. 1: H304

Most important adverse effects: Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.

Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long

lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

[cont...]

PVCU SOLVENT CLEANER

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS08: Health hazard
GHS07: Exclamation mark
GHS09: Environmental









Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/Physician. P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/Soap.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P102: Keep out of reach of children.
P273: Avoid release to the environment.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
2	65-151-9	64742-49-0	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224;	30-50%
				Skin Irrit. 2: H315; Aquatic Chronic 2:	
				H411	

N-BUTYL ACETATE - REACH registered number(s): 01-2119485493-29

204-658-1	123-86-4	Substance with a Community	Flam. Liq. 3: H226; STOT SE 3: H336;	10-30%
		workplace exposure limit.	-: EUH066	

ETHANOL - REACH registered number(s): 01-2119475610-43

200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	10-30%
		workplace exposure limit.		

PVCU SOLVENT CLEANER

Page: 3

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY

265-185-4	64742-82-1	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; Aquatic Chronic 2: H411	1-10%
2-BUTOXYET	HANOL			
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
METHANOL -	REACH registere	ed number(s): 01-2119433	307-44	
200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye

open. Remove any contact lenses and open eyes wide apart. Get medical attention if

any discomfort continues

Ingestion: Wash out mouth with water. If patient is conscious, give water to drink. If patient feels

unwell, seek medical advice.DO NOT INDUCE VOMITING.

Inhalation: Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid

or complete, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

PVCU SOLVENT CLEANER

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Original container stored in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s): No data available.

PVCU SOLVENT CLEANER

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL		
UK	724	966	-	-		

ETHANOL

UK	1920 mg/m3	-	-	-
----	------------	---	---	---

2-BUTOXYETHANOL

UK	25 ppm	50 ppm	-	-

METHANOL

UK	266 mg/m3	333 mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

N-BUTYL ACETATE

			1	
Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	960 mg/m3	Workers	Local
DNEL	Inhalation	480 mg/m3	Workers	Systemic
DNEL	Inhalation	859.7 mg/m3	Consumers	Local
DNEL	Inhalation	102.34	Consumers	Systemic
PNEC	Fresh water	0.18 mg/l	-	-
PNEC	Marine water	0.018 mg/l	-	-
PNEC	Microorganisms in sewage	35.6 mg/l	-	-
	treatment			
PNEC	Fresh water sediments	0.981 mg/kg	-	-
PNEC	Marine sediments	0.0981 mg/kg	-	-
PNEC	Soil (agricultural)	0.0903 mg/kg	-	-

METHANOL

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	40 mg/kg/day	Workers	Systemic
DNEL	Inhalation	260 mg/m3	Workers	Systemic
DNEL	Dermal	40 mg/kg/day	Workers	Local

PVCU SOLVENT CLEANER

Page: 6

DNEL	Inhalation	260 mg/m3	Workers	Local
DNEL	Dermal	8 mg/kg/day	Consumers	Systemic
DNEL	Inhalation	50 mg/m3	Consumers	Systemic
DNEL	Oral	8 mg/kg/day	Consumers	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition. In case of insufficient ventilation,where exposure to high concentrations of vapour is possible,suitable respiratory protective equipment

with positive air supply should be used.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. In case of

insufficient ventilation, wear suitable respiratory equipment.

Hand protection: Impermeable gloves, change regularly to avoid permeation problems. Ensure gloves

are manufactured/tested in accordance with BS EN 374.

Eye protection: Safety goggles. Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: Do not flush into surface water or sanitary sewer system. If the product contaminates

rivers and lakes or drains inform respective authorities.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Hydrocarbon

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Slightly soluble

Also soluble in: Acetone.

Viscosity: No data available.

Boiling point/range°C: 78.4-115.4 **Melting point/range°C:** No data available.

Flammability limits %: lower: 3.3 upper: 19.0

Flash point°C: 12 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >230 Vapour pressure: 5.8 kPa

Relative density: 0.774 pH: Approx 7

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

PVCU SOLVENT CLEANER

Page: 7

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

METHANOL

IVN RAT LD50 2131 mg/kg	IVN	RAT	LD50	2131	mg/kg
-------------------------	-----	-----	------	------	-------

PVCU SOLVENT CLEANER

Page: 8

ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

PVCU SOLVENT CLEANER

Page: 9

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(Hydrocarbons, C7-C9,n-alkanes,isoalkanes,cyclics,butyl acetate,ethanol)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E **Transport category:** 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

PVCU SOLVENT CLEANER

Page: 10

H319: Causes serious eye irritation.

H331: Toxic if inhaled. H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.